post@onsagers.no

ONSAGERS Ltd. Charles House 5 Regent Street London SW1Y 4LR UK Tel: +44 (0) 20 78 39 74 07 Fax: +44 (0) 20 78 39 64 46 mail@onsagers.com

RECEIVED **CENTRAL FAX CENTER**

DEC 2 9 2005

Bergen, Norway 29 December 2005

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450 USA

Our ref.: P16982US00 Christian Abel

Your ref:

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application serial no.:

10/717461

Inventor:

Kjell-Tore Smith

Øyvind Hammer Johansen

Erlend Skjold Richard Gjersøe

For:

Pressable plastic-bound explosive composition

Group No.: Examiner:

Attorney docket no.:

115700

RESPONSE TO ELECTION/RESTRICTION REQUIREMENT

In response to the Office Action of 12/07/2005, applicant hereby makes the following elections, under PARTIAL TRAVERSE.

TRAVERSE

Applicant respectfully traverses the first election requirement between Species A (Hy Temp 4454) and Species B (Hy Temp 4054).

As stated in the enclosed Product Specification from manufacturer Zeon Chemicals, Louisville, KY, HyTemp 4454 and HyTemp 4054 are in fact the same composition, but in various states of pulverization. As stated therein, "HyTemp 4454 is a ground form of HyTemp 4054"

Based on the foregoing, applicant believes a restriction between the two identified Species is unnecessary. In the event the examiner maintains the requirement, applicant conditionally elects Species A.

ELECTION

The above traverse is solely related to the election of elastomer species. With regard to the plasticizer species, applicant elects Species a.

www.onsagers.no

Therefore, in the event the examiner maintains the requirement with regards to the elastomer, the conditionally elected species combination is Aa.

CLAIMS READABLE ON THE ELECTED SPECIES

It is believed that all claims read on the elected species/conditionally elected species combination.

ADVOKATFIRMA HARRIS

Please charge any and all necessary fees during the pendancy of this application to deposit account 501898.

Respectfully Submitted,

ONSAGERS AS

Christian D. Abel

Reg no. 43,455

Cust. No. 29078

Certification of Facsimile Transmission and statement under 37 CFR 1.8(b)(3)

I hereby certify that the above-identified papers are being facsimile transmitted to the Patent and Trademark Office at

(571) 273-8300 on the date shown below:

Date:

I further hereby attest that I have personal knowledge that the papers have been transmitted on this date.

Christian D. Abel 43, 455

, Faks sendt av: +47 55302701

HyTempTM 4454

Temporary Product Specification Date Issued: 09/23/03 Supersedes: 04/07/03

Description: HyTemp 4454 is a ground form of HyTemp 4054, which contains one or more acrylic esters with a small percentage of a carboxy/chlorine cure site.

Packaging: The standard unit is an 800 lb. (362.9 Kg) cell box containing sixteen 50 lb. (22.68 Kg) units.				
Specification	Min.	Max.	Target	Zeon Test Procedure No. (1)
Polymer Properties				
Heat Loss (%)	0.0	0.5	0.2	1339
Ash (%)	0.0	0.6	0.4	873 (ASTM D-1416)
Mooney Viscosity ML (1+4) @ 100°C unmassed	22	34	28	404 (ASTM D-1646)
Glass Transition Temp. (°C)	-40.6	-31.7	-36.2	1273
Gel (%)	0.0	20	2	1251
Ground Rubber Properties]	İ		
Ash (%)	2	.7	3	873
Test Recipe Properties	1		}	1229
ODR (2)	1			1148
M _L (Ibfin)	4.7	7.4	6.0	
M _H (lbfin)	15.0	27.6	21.3	
tsl (min)	0.4	1.0	0.7	1
t'90 (min)	3.7	10.8	7.3	·

Special Notes: Refer to the appropriate MSDS for handling instructions.

- (1) Zeon Test Recipe and Procedures are available upon request
- (2) ASTM D-2084
- (3) Shelf Life retest critical parameters 2 years from date of manufacture for polymer properties and recheck 6 months for form

Reason for Issue: 1) Revised Glass Transition Temperature test procedure number from 1199 to 1273 as the 1199 is not the correct procedure number.

